



PRO[®]
GRIP
IT NEVER LETS GO

AQUASEAL

TECHNICAL DATA SHEET

PURPOSE

PRO GRIP AQUASEAL® is a ready to use quick drying polymer dispersion designed to form a waterproofing layer under ceramic, porcelain, stone and mosaic tiles. **PRO GRIP AQUASEAL®** may be applied onto balconies, terraces and in bathrooms, shower cubicles, laundry rooms, saunas etc. This product is highly flexible, resistant to water and common cleaning products. Tiles must be installed onto the waterproofed surface with a high quality polymer modified adhesive (e.g. **PRO GRIP SUPERBOND 12 ADHESIVE** or **PRO GRIP TILE ON TILE ADHESIVE**) to ensure a good bond and superior water resistance.

- **FLEXIBLE WATERPROOFING COATING**



AQUASEAL TECHNICAL DATA SHEET

**PRO
GRIP**[®]
IT NEVER LETS GO

MIXING INSTRUCTIONS

PROGRIP AQUASEAL® is a ready to use product and it must not be diluted with water or any other substance.

SURFACE PREPARATION

These recommendations are in accordance with the SABS standard SANS 10107:2011 - The design and installation of ceramic tiles

- a. Ensure that surfaces to be tiled are sound (no cracks or crumbling), clean, free of dust, release agent, fungi, or any surface dampness. Fungi must be removed and the spores killed with the use of an effective fungicide. (A dilution of household bleach is sufficient)
- b. New walls and floors must be allowed to cure for minimum periods as listed below to ensure that movement due to shrinkage does not affect the installation.

Direct bedding onto new brick walls and concrete surfaces:	6 weeks
Newly plastered wall	2 weeks
Newly screeded floors:	4 weeks

- c. Very smooth surfaces such as steel trowelled and off-shutter concrete must be acid washed to remove laitance and then rinsed thoroughly with cold water.
- d. Painted surfaces, gypsum plasters and surfaces that have old bitumen adhesive on them must be chipped in order to expose at least 80% of the substrate.
- e. Highly porous substrates can negatively affect the bond strength between the substrate and the coating. Check the porosity of the substrate by applying a small quantity of water. If the moisture is completely absorbed within one minute, then the surface is too porous and will need to be sealed with a mixture of 2 parts **PROGRIP BASECOAT®** mixed with one part **PROGRIP KEYCOAT®** and allowed to dry prior to applying **PRO GRIP AQUASEAL®**.

*This guideline only serves as a basic manual for the surface preparation, product selection and installation procedure for this type of application. Each installation needs to be assessed on merits and the products used and the procedures followed should be in accordance with the SABS code for the design and installation of ceramic tiles (SABS 10107:2011).



AQUASEAL

TECHNICAL DATA SHEET

**PRO
GRIP**[®]
IT NEVER LETS GO

PRODUCT APPLICATION

1. **PRO GRIP AQUASEAL**[®] must be applied in two even coats with a longhaired paint roller or brush.
2. The first coat must be dry before applying the second coat at a 90 degree angle to the first coat.
3. Make sure that there are no breaks in the coating due to surface imperfections prior to applying the second coat or prior to tiling.
4. **PRO GRIP AQUASEAL**[®] may be applied to vertical sloping surfaces.
5. Pay attention to any expansion joints and the joints between horizontal and vertical surfaces. In these areas, bed **PRO GRIP WATERPROOFING MEMBRANE** into the first coat of **PRO GRIP AQUASEAL**[®] to provide added protection.

GENERAL APPLICATION INFORMATION

1. Carefully inspect the surface of the **PRO GRIP AQUASEAL**[®] before tiling. Make sure that there are no pinpricks or breaks in the coating. If there are any surface defects, apply an additional coat.
2. Tiles must be laid with a polymer modified tile adhesive to ensure an effective bond and additional water resistance. Suitable products are **PRO GRIP SUPERBOND 12 ADHESIVE**[®], **PRO GRIP TILE ON TILE ADHESIVE**[®] or **PRO GRIP STONE AND GLASS MOSAIC ADHESIVE**[®].
3. Application onto a hot concrete surface in direct sunlight may result in the formation of pinpricks in the **PRO GRIP AQUASEAL**[®] surface. Rather apply **PRO GRIP AQUASEAL**[®] to exterior surfaces during the early morning.
4. Fill the standard tile joints with **PRO GRIP WATERPROOF GROUT**[®] and expansion joints with **PRO GRIP FLEXIBLE EXPANSION JOINT**[®] for additional waterproofing protection.
5. Brushes and rollers must be cleaned with water before the product has dried.

*This guideline only serves as a basic manual for the surface preparation, product selection and installation procedure for this type of application. Each installation needs to be assessed on merits and the products used and the procedures followed should be in accordance with the SABS code for the design and installation of ceramic tiles (SABS 10107:2011).



AQUASEAL

TECHNICAL DATA SHEET

PRO GRIP[®]
IT NEVER LETS GO








PRECAUTIONS & LIMITATIONS

- a. Ensure that the above instructions are adhered to at all times and do not adulterate the product in any way as this could result in failure.
- b. Rubber gloves should be used when applying **PRO GRIP AQUASEAL**[®]. In the event of irritation, rinse skin under cold water. Consult a doctor if irritation persists.
- c. Keep **PRO GRIP AQUASEAL**[®] away from pets and children.
- d. Do not ingest and do not empty surplus grout down drains.



TECHNICAL DATA

(@ 25°C & 50% Humidity) Cold temperatures or non-porous substrates or tiles may extend the open and setting times.

Type		Paste
Colour when set		White
Final Drying Time		1 hour between coats at 25°C and 50% humidity 4 hours before applying tiles at 25°C and 50% humidity 12 hours for full cure at 25°C and 50% humidity
Coverage		± 3.5m ² per 5 Lt bucket (two coats)
Packaging		2 Lt and 5 Lt buckets
Storage		Keep container closed when not in use. Store at a moderate temperature.
Shelf life		12 months under moderate temperature

*This guideline only serves as a basic manual for the surface preparation, product selection and installation procedure for this type of application. Each installation needs to be assessed on merits and the products used and the procedures followed should be in accordance with the SABS code for the design and installation of ceramic tiles (SABS 10107:2011).